



Firma: BIZ GROUP DOO BEOGRAD
Adresa: Kapetana Radiča Petrovića 32b
Telefon: 011 452 52 66, 060 452 52 66
Fax:
PIB: 111338015
E-mail: office@bizgroup.rs

MB ASUS AMD AM4 PRIME A520M-K

Šifra: 21117

Kategorija proizvoda: Matične ploče za AMD socket

Proizvođač: ASUS

Cena: **10.907,00** din.



CPU

Build in AMD AM4 Socket Processors *

* Refer to www.asus.com for CPU support list

Chipset

AMD A520

Graphic

1 x D-Sub

1 x HDMI 2.1(4K@60HZ)

Memor

2 x DIM

4600(C

MHz H

Expan

3rd Ge

with R

1 x Refe

AMD

* The n

proces

Storage

Total supports 1 x M.2 slot(s) and 4 x SATA 6Gb/s ports

3rd Gen AMD Ryzen™ and 3rd Gen AMD Ryzen™ with Radeon™ Graphics Processors :

1 x M.2 Socket 3, with M Key, Type 2242/2260/2280 (PCIe 3.0 x4 and SATA modes) storage devices support

AMD A520 Chipset :

4 x SATA 6Gb/s port(s),

Support Raid 0, 1, 10

Audio

Realtek ALC887 7.1 Surround Sound High Definition Audio CODEC *

- Supports : Jack-detection, Multi-streaming, Front Panel Jack-retasking, up to 24-Bit/192kHz playback

Audio Feature :

- Audio Shielding

- Dedicated audio PCB layers

* Choose the chassis with HD audio module in front panel to support 8-channel audio output.

Software Features

ASUS Exclusive Software

Armoury Crate

AI Suite 3

- Performance and Power Saving Utility

TurboV EVO

EPU

Digi+ VRM

Fan Xpert

LAN

Realtek

ASUS L

USB Po

Rear U

4 x US

2 x US

Front

2 x US

4 x US

- EZ update	ASUS Special Features	Back I/O
ASUS CPU-Z	ASUS 5X PROTECTION III	1 x PS/2
AI Charger	- ASUS DIGI+ VRM	1 x D-Sub
DAEMON Tools	- ASUS LANGuard	1 x HD-DVI
Norton Anti-virus software (Free Trial for 60 days)	- ASUS Overvoltage Protection	1 x LAN
WinRAR	- ASUS SafeSlot Core	4 x USB
UEFI BIOS	- ASUS Stainless-Steel Back I/O	2 x USB
ASUS EZ DIY	ASUS Q-Design	3 x Audio
- ASUS CrashFree BIOS 3	- ASUS Q-DIMM	
- ASUS EZ Flash 3	- ASUS Q-Slot	
- ASUS UEFI BIOS EZ Mode	ASUS Thermal Solution	
	- Aluminum heatsink design	
	Internal I/O Ports	Accessories
	1 x CPU Fan connector(s)	User's Manual
	1 x Chassis Fan connector(s)	I/O Shield
	1 x USB 3.2 Gen 1(up to 5Gbps) connector(s) support(s) additional 2 USB 3.2 Gen 1 port(s)	2 x SATA
	2 x USB 2.0 connector(s) support(s) additional 4 USB 2.0 port(s)	1 x Super SATA
	1 x M.2 Socket 3 with M key, type 2242/2260/2280 storage devices support (SATA & PCIE 3.0 x 4 mode)	1 x M.2
	1 x SPI TPM header	
	4 x SATA 6Gb/s connector(s)	
	1 x S/PDIF out header(s)	
	1 x 24-pin EATX Power connector(s)	
	1 x 8-pin EATX 12V Power connectors	
	1 x Front panel audio connector(s) (AAFP)	
	1 x Clear CMOS jumper(s)	
	1 x System panel connector	
	1 x COM port header	
	1 x Speaker connector	
	BIOS	Management Software
	256 Mb Flash ROM, UEFI AMI BIOS	WOL by LAN
	Operating System	Form Factor
	Windows® 10 64-bit	mATX
		8.9 inch