



Firma: BIZ GROUP DOO BEOGRAD
Adresa: Kapetana Radiča Petrovića 32b
Telefon: 011 452 52 66, 060 452 52 66
Fax:
PIB: 111338015
E-mail: office@bizgroup.rs

MB AsRock AMD AM4 B450M-HDV R4.0

Šifra: 21474

Kategorija proizvoda: Matične ploče za AMD socket

Proizvođač: ASROCK

Cena: **7.435,00** din.



ASRock Super Alloy

- High Density Glass Fabric PCB
- Sapphire Black PCB

ASRock Ultra M.2 (PCIe Gen3 x4 & SATA3)

ASRock Full Spike Protection (for all USB, Audio, LAN Ports)

ASRock Live Update & APP Shop

CPU

- Supports AMD AM4 Socket Ryzen™ 2000, 3000 and 5000 Series Desktop Processors
- 6 Power Phase design
- Supports CPU up to 105W

Chipset

- AMD

Memory

- Dual Channel DDR4 Memory Technology
- 2 x DDR4 DIMM Slots
- AMD Ryzen series CPUs (Matisse) support DDR4 3200 / 2933 / 2667 / 2400 / 2133 ECC & non-ECC, un-buffered memory*
- AMD Ryzen series CPUs (Pinnacle Ridge) support DDR4 3200+(OC) / 2933(OC) / 2667 / 2400 / 2133 ECC & non-ECC, un-buffered memory*
- AMD Ryzen series CPUs (Picasso) support DDR4 2933 / 2667 / 2400 / 2133 non-ECC, un-buffered memory*
- AMD Ryzen series CPUs (Summit Ridge) support DDR4 3200+(OC) / 2933(OC) / 2667 / 2400 / 2133 ECC & non-ECC, un-buffered memory*
- AMD Ryzen series CPUs (Raven Ridge) support DDR4 3200+(OC) / 2933 / 2667 / 2400 / 2133 non-ECC, un-buffered memory*
- Max. capacity of system memory: 64GB*
- Supports Extreme Memory Profile (XMP) memory modules
- 15µ Gold Contact in DIMM Slots

*For Ryzen Series CPUs (Picasso and Raven Ridge), ECC is only supported with PRO CPUs.
Please refer to below table for DDR4 UDIMM maximum frequency support.

Ryzen Series CPUs (Matisse):

UDIMM Memory Slot		Frequency (Mhz)
A1	B1	
SR	-	3200
-	SR	3200
DR	-	3200
-	DR	3200
SR	SR	3200
DR	DR	3200

Ryzen Series CPUs (Pinnacle Ridge):

UDIMM Memory Slot		Frequency (Mhz)
A1	B1	
SR	-	2933
-	SR	2933
DR	-	2933
-	DR	2933
SR	SR	2933
DR	DR	2933

Ryzen Series CPUs (Picasso):

UDIMM Memory Slot		Frequency (Mhz)
A1	B1	
SR	-	2933
-	SR	2933
DR	-	2667
-	DR	2667
SR	SR	2933
DR	DR	2667

Ryzen Series CPUs (Summit Ridge):

UDIMM Memory Slot		Frequency (Mhz)
A1	B1	
SR	-	2667
-	SR	2667
DR	-	2667
-	DR	2667
SR	SR	2667
DR	DR	2667

Ryzen Series CPUs (Raven Ridge):

UDIMM Memory Slot		Frequency (Mhz)
A1	B1	
SR	-	2933
-	SR	2933
DR	-	2667
-	DR	2667
SR	SR	2933
DR	DR	2667

SR: Single rank DIMM, 1Rx4 or 1Rx8 on DIMM module label

DR: Dual rank DIMM, 2Rx4 or 2Rx8 on DIMM module label

**Due to the operating system limitation, the actual memory size may be less than 4GB for the reservation for system usage under Windows® 32-bit OS. For

Windows® 64-bit OS with 64-bit CPU, there is no such limitation.

BIOS

- 128Mb AMI UEFI Legal BIOS with GUI support
- Supports "Plug and Play"
- ACPI 5.1 compliance wake up events
- Supports jumperfree
- SMBIOS 2.3 support
- DRAM Voltage multi-adjustment

Audio

- 7.1 CH HD Audio (Realtek ALC887/897 Audio Codec)
- Supports Surge Protection

Slots

AMD Ryzen series CPUs (Matisse, Summit Ridge and Pinnacle Ridge)

- 1 x PCI Express 3.0 x16 Slot (PCIE2: x16 mode)*

AMD Ryzen series CPUs (Picasso, Raven Ridge)

- 1 x PCI Express 3.0 x16 Slot (PCIE2: x8 mode)*

AMD Athlon series CPUs

- 1 x PCI Express 3.0 x16 Slot (PCIE2: x4 mode)*

- 1 x PCI Express 2.0 x1 Slot

*Supports NVMe SSD as boot disks

Connector

- 1 x COM Port Header
- 1 x TPM Header
- 1 x Chassis Intrusion and Speaker Header
- 1 x CPU Fan Connector (4-pin)*
- 2 x Chassis Fan Connectors (1 x 3-pin, 1 x 4-pin)**
- 1 x 24 pin ATX Power Connector
- 1 x 4 pin 12V Power Connector
- 1 x Front Panel Audio Connector
- 2 x USB 2.0 Headers (Support 4 USB 2.0 ports) (Supports ESD Protection)
- 1 x USB 3.1 Gen1 Header (Supports 2 USB 3.1 Gen1 ports) (Supports ESD Protection)

*The CPU Fan Connector supports the CPU fan of maximum 1A (12W) fan power.

**The Chassis Fan Connector supports the chassis fan of maximum 1A (12W) fan power.

Software and UEFI

Software

- ASRock A-Tuning
- ASRock XFast LAN

UEFI

- ASRock Full HD UEFI
- ASRock Instant Flash
- ASRock Easy RAID Installer

*These utilities can be downloaded from ASRock Live

Graphi

- Integr
- Ryzen
- Direct
- Share
- suppor
- Three
- LAN
- Supp
- PCI
- (4096x
- Supp
- @500H
- Supp
- @500H
- Supp
- and HB
- (Compl
- Supp
- Supp

*Actua

**The M

memor

Storage

- 4 x SA
- RAID 1
- 1 x UL
- 2242/2
- PCI Exp
- Matisse
- Pinnac
- APU)*

*Suppo

Support

Rear Pa

- 1 x PS

- 1 x D

- 1 x D

- 1 x H

- 2 x US

- 4 x US

- 1 x RJ

LED)

- HD Au

Update & APP Shop.

Support CD

- Drivers, Utilities, AntiVirus Software (Trial Version),
Google Chrome Browser and Toolbar

Hardware Monitor

- CPU/Chassis temperature sensing
- CPU/Chassis Fan Tachometer
- CPU/Chassis Quiet Fan
- CPU/Chassis Fan multi-speed control
- CASE OPEN detection
- Voltage monitoring: +12V, +5V, +3.3V, Vcore

Access

- Quick
- 2 x SA
Form
- Micro
cm
- Solid