



Firma: BIZ GROUP DOO BEOGRAD  
Adresa: Kapetana Radiča Petrovića 32b  
Telefon: 011 452 52 66, 060 452 52 66  
Fax:  
PIB: 111338015  
E-mail: office@bizgroup.rs

## MB AM4 TUF GAMING B550-PLUS

Šifra: 22894

Kategorija proizvoda: Matične ploče za AMD socket

Proizvođač: ASUS

Cena: **16.965,00** din.



Podnožje:	AMD® AM4
Čipset:	AMD® B550
Tip procesora:	AMD
Format ploče:	ATX
Podržani procesori:	- AMD Ryzen procesori treće generacije sa AM4 podnožjem
Podržana memorija:	DDR4
Memorija:	3rd Gen AMD Ryzen™ Processors - 4 x DIMM, Max. 128GB, DDR4 4600(O.C.)/4400(O.C.)/4266(O.C.)/4133(O.C.)/4000(O.C.)/3866(O.C.)/3733(O.C.)/3600(O.C.)/3466(O.C.) Memory - Next Generation AMD Ryzen PRO Processors 4 x DIMM, Max. 128GB, DDR4 4800(O.C.)/4600(O.C.)/4466(O.C.)/4400(O.C.)/4266(O.C.)/4133(O.C.)/4000(O.C.)/3866(O.C.)/3733(O.C.) MHz Un-buffered Memory - Dual Channel Memory Architecture
Multi-GPU podrška:	- AMD 2-Way CrossFireX Technology
Integrirana grafička karta:	- 1 x DisplayPort 1.4 - 1 x HDMI 2.1(4K@60HZ)
Slotovi za proširenje:	3rd Gen AMD Ryzen Processors - 1 x PCIe 4.0 x16 (x16 mode) AMD B550 Chipset - 1 x PCIe 3.0 x16
Skladište:	Ukupno podržano 2 x M.2 slota i 6 x SATA 6Gb/s portova 3rd Gen AMD Ryzen Processors: - 1 x M.2 slot, with B key, type 2242/2260 support(SATA & PCIe 4.0 x4 mode) AMD B550 Chipset: - 1 x M.2 Socket 3, with M key, type 2242/2260 6 x SATA 6Gb/s port(s) - Podržava Raid 0, 1, 10
Mrežna karta:	- Realtek RTL8125B 2.5Gb Ethernet - TUF LANGuard
Zvučna karta:	- Realtek ALC S1200A 7.1 Surround Sound High Definition Audio CODEC
USB:	Rear USB Port ( Total 8 ) - 2 x USB 3.2 Gen 2 port(s)(1 x Type-A +1 x USB Type-C) - 4 x USB 3.2 Gen 1 port(s)(4 x Type-A) Total 6 ) - 2 x USB 3.2 Gen 1 port(s)(2 x Type-A) - 4 x USB 2.0 port(s)(4 x Type-A)
Konektori na zadnjoj strani:	- 1 x DisplayPort - 1 x HDMI - 1 x LAN (2.5G) port(s) - 2 x USB 3.2 Gen 2 (teal blue) (1 x Type-A+1 x Type-C) can be switched to USB BIOS FlashBack) - 1 x Optical S/PDIF out - 5 x Audio jack(s) - 1 x BIOS FlashBack

Interni konektori:	- 1 x CPU Fan connector(s) - 1 x CPU OPT Fan connector(s) - 3 x Chassis Fan connector(s) - 1 x AIO_ header(s) - 1 x USB 3.2 Gen 1(up to 5Gbps) connector(s) support(s) additional 2 USB 3.2 Gen 1 port 1 x M.2 Socket 3 with M key, type 2242/2260/2280/22110 storage devices support(SATA & PCIe 4.0 storage devices support (SATA & PCIE 3.0 x 4 mode) - 1 x M.2 with E key for Wi-Fi module - 1 x SPI connector(s) - 1 x 8-pin EATX 12V Power connectors - 1 x Front panel audio connector(s) (AAFP) - 1 System panel connector - 1 x COM port header
--------------------	--