



Firma: BIZ GROUP DOO BEOGRAD
Adresa: Kapetana Radiča Petrovića 32b
Telefon: 011 452 52 66, 060 452 52 66
Fax:
PIB: 111338015
E-mail: office@bizgroup.rs

MB AM4 GIGABYTE B550M DS3H

Šifra: 21959
Kategorija proizvoda: Matične ploče za AMD socket
Proizvođač: GIGABYTE

Cena: **13.373,00** din.



CPU

AMD Socket AM4,
support for: AMD
Ryzen™ 5000 Series/
Ryzen™ 5000 G-Series/
Ryzen™ 4000 G-Series
and Ryzen™ 3000 Series
Processors

(Please refer "CPU Support List" for more information.)

Chipset

AMD B550

Onboard Graphics

Integrated Graphics Processor:

1 x DVI-D port,
supporting a maximum
resolution of
1920x1200@60 Hz
* The DVI-D port does
not support D-Sub
connection by adapter.

1 x HDMI port,
supporting a maximum
resolution of
4096x2160@60 Hz
* Support for HDMI 2.1
version, HDCP 2.3, and
HDR.

Memor

4 x D
supp
(32 G
capac
mem

Audio

Maximum shared memory of 16 GB

(Please
informa

Realtek® Audio CODEC

High Definition Audio
2/4/5.1/7.1-channel
* To configure 7.1-channel audio, you need to open the audio software and select Device advanced settings > Playback Device to change the default setting first. Please visit GIGABYTE's website for details on configuring the audio software.

LAN

Realtek® GbE LAN chip
(1000 Mbit/100 Mbit)

Expans
1 x PCI
CPU:
AMD
Serie
Serie
supp
mode

Storage Interface

1 x M.2 connector (M2A_CPU), integrated in the CPU, supporting Socket 3, M key, type 2242/2260/2280/22110 SSDs:

AMD Ryzen™ 5000 Series and Ryzen™ 3000 Series Processors support SATA and PCIe 4.0 x4/x2 SSDs

AMD Ryzen™ Ryzen™ 5000 G-Series and Ryzen™ 4000 G-Series Processors support SATA and PCIe 3.0 x4/x2 SSDs

USB
CPU:
4 x U
on th
1 x PCI
Chipse
2 x U
Supp
avail
mode
1 x PCI
Chipse
Supp
mode

1 x M.2 connector (M2B_SB), integrated in the Chipset, supporting Socket 3, M key, type 2242/2260/2280 SSDs:

Supporting SATA and PCIe 3.0 x2 SSDs

4 x SATA 6Gb/s connectors, integrated in the Chipset: Support for RAID 0, RAID 1, and RAID 10

Internal I/O Connectors

1 x 24-pin ATX main power connector

1 x 8-pin ATX 12V power connector

1 x CPU fan header

2 x system fan headers

2 x addressable LED

strip headers

2 x RGB LED strip

headers

1 x CPU cooler LED

strip/RGB LED strip

header

2 x M.2 Socket 3

connectors

4 x SATA 6Gb/s

connectors

1 x front panel header

1 x front panel audio

header

1 x USB 3.2 Gen 1

header

1 x USB 2.0/1.1 header

1 x Trusted Platform

Module (TPM) header
(2x6 pin, for the GC-
TPM2.0_S module only)

1 x serial port header

1 x Clear CMOS jumper
1 x Q-Flash Plus button

Back Panel Connectors
1 x PS/2
keyboard/mouse port

1 x DVI-D port

1 x HDMI port
4 x USB 3.2 Gen 1 ports
4 x USB 2.0/1.1 ports
1 x RJ-45 port
3 x audio jacks

I/O Con
iTE®

*All fan headers are subject to support AIO_Pump, Pump
and high performance fan with the capability of
delivering up to 2A/12V @ 24W.

H/W Monitoring
Voltage detection

Temperature detection
Fan speed detection
Overheating warning
Fan fail warning
Fan speed control
* Whether the fan speed
control function is
supported will depend
on the cooler you install.

BIOS
1 x 2

Unique Features

Support for APP Center
* Available applications
in APP Center may vary
by motherboard model.
Supported functions of
each application may
also vary depending on
motherboard
specifications.
@BIOS
EasyTune
Fast Boot
Game Boost
ON/OFF Charge
RGB Fusion
Smart Backup
System Information
Viewer

Support for Q-Flash Plus

Bundle
Norto
Secur

Support for Q-Flash
Support for Xpress Install

Operating System
Support for Windows 10
64-bit

Form F
Micro
24.4c