



Firma: BIZ GROUP DOO BEOGRAD
Adresa: Kapetana Radiča Petrovića 32b
Telefon: 011 452 52 66, 060 452 52 66
Fax:
PIB: 111338015
E-mail: office@bizgroup.rs

LAN Router TP-LINK ARCHER C54 AC1200,4-5GHz4 anteneAPRE

Šifra: 24725
Kategorija proizvoda: Ruteri i ekstenderi
Proizvođač: TP-Link

Cena: **4.352,00** din.



WIRELESS	
Standards	Wi-Fi 5 IEEE 802.11ac/n/a 5 GHz IEEE 802.11n/b/g 2.4 GHz
WiFi Speeds	AC1200 5 GHz: 867 Mbps (802.11ac) 2.4 GHz: 300 Mbps (802.11n)
WiFi Range	3 Bedroom Houses 4x Fixed Antennas Multiple antennas form a signal-boosting array to cover more directions and large areas Beamforming Concentrates wireless signal strength towards clients to expand WiFi range
WiFi Capacity	Medium Dual-Band Allocate devices to different bands for optimal performance MU-MIMO Simultaneously communicates with multiple MU-MIMO clients
Working Modes	Router Mode Access Point Mode Range Extender Mode
HARDWARE	
Processor	Single-Core CPU
Ethernet Ports	1x 10/100 Mbps WAN Port 4x 10/100 Mbps LAN Ports
Buttons	WPS/Reset Button
Power	9 V ? 0.85 A
SECURITY	
WiFi Encryption	WPA WPA2 WPA3 WPA/WPA2-Enterprise (802.1x)

SECURITY	
Network Security	SPI Firewall Access Control IP & MAC Binding Application Layer Gateway
Guest Network	1× 5 GHz Guest Network 1× 2.4 GHz Guest Network
SOFTWARE	
Protocols	IPv4 IPv6
Parental Controls	URL Filtering Time Controls
WAN Types	Dynamic IP Static IP PPPoE PPTP L2TP
Quality of Service	QoS by Device
NAT Forwarding	Port Forwarding Port Triggering DMZ UPnP
IPTV	IGMP Proxy IGMP Snooping Bridge Tag VLAN
DHCP	Address Reservation DHCP Client List Server
DDNS	NO-IP DynDNS
Management	Tether App Webpage Check Web Emulator>
PHYSICAL	
Dimensions (W×D×H)	4.5 × 4.2 × 1.0 in (115 × 106.7 × 24.3 mm)
Package Contents	Wi-Fi Router Archer C54 Power Adapter RJ45 Ethernet Cable Quick Installation Guide
OTHER	
System Requirements	Internet Explorer 11+, Firefox 12.0+, Chrome 20.0+, Safari 4.0+, or other JavaScript-enabled browser Cable or DSL Modem (if needed) Subscription with an internet service provider (for internet access)
Certifications	FCC, CE, RoHS
Environment	Operating Temperature: 0?~40? (32? ~104?) Storage Temperature: -40?~60? (-40? ~140?) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing
TEST DATA	
WiFi Transmission Power	CE EIRP: <20dBm(2.4GHz) <23dBm(5GHz) FCC: <30dBm(2.4GHz & 5GHz)

TEST DATA**WiFi Reception Sensitivity**

5GHz:
11a 6Mbps:-93dBm;
11a 54Mbps:-78dBm;
11ac HT20 mcs8:69dBm;
11ac HT40 mcs9:-66dBm;
11ac HT80 mcs9:-62dBm;
2.4GHz:
11g 54Mbps:-78dBm;
11n HT20 mcs7:-74dBm;
11n HT40 mcs7:-71dbm;