



Firma: BIZ GROUP DOO BEOGRAD
Adresa: Kapetana Radiča Petrovića 32b
Telefon: 011 452 52 66, 060 452 52 66
Fax:
PIB: 111338015
E-mail: office@bizgroup.rs

LAN Router TP-LINK ARCHER C54 AC1200,4-5GHz4 anteneAPRE

Šifra: 24725
Kategorija proizvoda: Ruteri i ekstenderi
Proizvođač: TP-Link

Cena: **4.352,00** din.



| WIRELESS | |
|------------------------|--|
| Standards | Wi-Fi 5 IEEE 802.11ac/n/a 5 GHz IEEE 802.11n/b/g 2.4 GHz |
| WiFi Speeds | AC1200 5 GHz: 867 Mbps (802.11ac) 2.4 GHz: 300 Mbps (802.11n) |
| WiFi Range | 3 Bedroom Houses 4x Fixed Antennas Multiple antennas form a signal-boosting array to cover more directions and large areas Beamforming Concentrates wireless signal strength towards clients to expand WiFi range |
| WiFi Capacity | Medium Dual-Band Allocate devices to different bands for optimal performance MU-MIMO Simultaneously communicates with multiple MU-MIMO clients |
| Working Modes | Router Mode Access Point Mode Range Extender Mode |
| HARDWARE | |
| Processor | Single-Core CPU |
| Ethernet Ports | 1x 10/100 Mbps WAN Port 4x 10/100 Mbps LAN Ports |
| Buttons | WPS/Reset Button |
| Power | 9 V ? 0.85 A |
| SECURITY | |
| WiFi Encryption | WPA WPA2 WPA3 WPA/WPA2-Enterprise (802.1x) |

| SECURITY | |
|--------------------------------|--|
| Network Security | SPI Firewall Access Control IP & MAC Binding Application Layer Gateway |
| Guest Network | 1× 5 GHz Guest Network 1× 2.4 GHz Guest Network |
| SOFTWARE | |
| Protocols | IPv4 IPv6 |
| Parental Controls | URL Filtering Time Controls |
| WAN Types | Dynamic IP Static IP PPPoE PPTP L2TP |
| Quality of Service | QoS by Device |
| NAT Forwarding | Port Forwarding Port Triggering DMZ UPnP |
| IPTV | IGMP Proxy IGMP Snooping Bridge Tag VLAN |
| DHCP | Address Reservation DHCP Client List Server |
| DDNS | NO-IP DynDNS |
| Management | Tether App Webpage Check Web Emulator> |
| PHYSICAL | |
| Dimensions (W×D×H) | 4.5 × 4.2 × 1.0 in (115 × 106.7 × 24.3 mm) |
| Package Contents | Wi-Fi Router Archer C54 Power Adapter RJ45 Ethernet Cable Quick Installation Guide |
| OTHER | |
| System Requirements | Internet Explorer 11+, Firefox 12.0+, Chrome 20.0+, Safari 4.0+, or other JavaScript-enabled browser Cable or DSL Modem (if needed) Subscription with an internet service provider (for internet access) |
| Certifications | FCC, CE, RoHS |
| Environment | Operating Temperature: 0?~40? (32? ~104?) Storage Temperature: -40?~60? (-40? ~140?) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing |
| TEST DATA | |
| WiFi Transmission Power | CE EIRP: <20dBm(2.4GHz) <23dBm(5GHz) FCC: <30dBm(2.4GHz & 5GHz) |

TEST DATA**WiFi Reception Sensitivity**

5GHz:
11a 6Mbps:-93dBm;
11a 54Mbps:-78dBm;
11ac HT20 mcs8:69dBm;
11ac HT40 mcs9:-66dBm;
11ac HT80 mcs9:-62dBm;
2.4GHz:
11g 54Mbps:-78dBm;
11n HT20 mcs7:-74dBm;
11n HT40 mcs7:-71dbm;